

Perfect choice for Access Control

Akuvox's S535 is crafted to deliver an eye-catching and user-friendly experience. Equipped with a host of advanced features, it serves as an entirely adaptable solution for managing access control for residents and visitors in a variety of settings, including condominiums, apartment complexes, office spaces, gated residential areas, and industrial facilities.

At a Glance

- Aluminum panel with 5-inch touchscreen;
- Linux operation system;
- Wide-angle camera: 116° (H), 62° (V);
- Two-way audio communication over IP networks with Echo Cancellation feature;
- Multi-way access feature including: Face, Fingerprint, EM/MIFARE Card, PIN, BLE & QR code;
- Features a 12V/500mA power output;
- Flush-mounted & surface-mounted;
- Complies with SIP & ONVIF;



Physical & Power

- | | |
|---|---|
| <ul style="list-style-type: none"> • Front Panel: Aluminum • Display: 5 Inch IPS LCD • Main Camera: 2M pixels, auto-lighting • Light Sensor: Support • Motion Sensor: Support • Wiegand Port: 1ch input/output(selectable) • RS485 Port: Support • RF reader: 13.56MHz&125kHz, NFC • Relays Out: 1 • Inputs: 2 • Microphone: 1 • Speaker: 1 • Reset: 1 | <ul style="list-style-type: none"> • BLE: Support BT5.0 • Tamper Alarm: Support • Fingerprint: Support • Ethernet Port: 1xRJ45, 10/100Mbps adaptive • 802.3at Power-over-Ethernet • Power supply: DC 12V / 3A • IP Rating: IP66 • IK Rating: IK08 • Installation: Flush-mounted & Wall-mounted • Dimension (HxWxD):260x100x27mm • Working Humidity: 10~90% • Working Temperature: -40°C ~ +55°C • Storage Temperature: -40°C ~ +70°C |
|---|---|

Audio

- SIP v1 (RFC2543), SIP v2 (RFC3261)
- Narrowband audio codec: G.711a, G.711μ
- Wideband audio codec: G.722
- DTMF: In-band, out-of-band DTMF (RFC2833), SIP Info
- Echo Cancellation
- Voice Activation Detection
- Comfort Noise Generator

Video

- Sensor: 1/2.9", CMOS for main camera
- Pixels: CIF, QCIF, VGA, 4CIF, 720p, 1080p
- Video codec: H.264
- Video technology: HDR
- Video resolution: up to 1920x1080
- Max. image transfer rate: 1080p – 30fps
- Viewing angle: 110°(H) / 62°(V)
- Compatible to 3rd-Party-Video components, e.g. NVRs

Networking & Protocol

- Protocols support: IPv4, HTTP, HTTPS, FTP, DNS, NTP, RTSP, RTP, TCP, UDP, ICMP, DHCP, ARP

Door Entry Feature

- Relays controlled individually by DTMF tones
- Multi-way Unlock: Face, EM/MIFARE Card, PIN, Fingerprint, BLE & QR code
- Camera permanently operational
- White balance: auto
- Minimum illumination: 0.1LUX

Capacity

- User: 20,000
- Face Templates: 20,000
- Finger Templates: 20,000
- Card: 100,000
- PIN: 50,000

Card Type

- EM card
- MIFARE card
- DESFire card (EV2/EV3)
- Felica card

Deployment & Maintenance

- Auto-Provisioning
- Web management portal
- Web-based packet dump
- Configuration backup / restore
- Access table export / import
- Firmware upgrade
- System logs (include door access logs)